



# BRITE-MARK<sup>®</sup> Roughneck

Permanent Paint Marker/Valve Action

## DIRECTIONS

- Shake well with cap on
- Depress tip to start flow
- Replace cap when not in use

## FEATURES

- BRITE-MARK<sup>®</sup> Roughneck is a general purpose paint marker that writes on almost any surface.
- BRITE-MARK<sup>®</sup> is available in 3 marker styles - BRITE-MARK<sup>®</sup> Medium, BRITE-MARK<sup>®</sup> Roughneck, BRITE-MARK<sup>®</sup> Threaded Cap
- Makes permanent bright marks on metal, rubber, plastic, glass, concrete, leather, stone, wood, vinyl and more.
- Quick drying, oil based, UV resistant paint withstands harsh indoor and outdoor conditions.
- Does not contain any HAP's (Hazardous Air Pollutants) which makes them a smart alternative to using spray paint and stencil for big, bold marks.
- Does not contain any reportable amounts of Xylene.
- Markers can be used to permanently identify inventory, assemblies, tools, finished products or work in progress while resisting most work related abuses or compounds.
- Valve action mechanism prevents paint in barrel from drying when the cap is left off.
- Bullet tips are replaceable to assure complete use of paint in each marker.
- BRITE-MARK<sup>®</sup> Roughneck markers have a heavy duty aluminum body with large paint capacity.
- BRITE-MARK<sup>®</sup> Roughneck has a tough polyester tip designed to write through grease, dirt, water and oil.

## MATERIALS COMPATIBILITY

- Safe on most surfaces.
- Removable with DYKEM<sup>®</sup> Remover & Cleaner.
- Surface tests should be run to determine compatibility prior to use.

## HEALTH AND SAFETY

- Flammable liquid and vapor. Keep away from heat, sparks and flame. Use only with adequate ventilation. Avoid contact with skin and eyes.
- Refer to SDS (Safety Data Sheet) for complete information on health and safety. Visit our website at [www.dykem.com](http://www.dykem.com) to obtain an MSDS.



## PHYSICAL PROPERTIES

Appearance / Physical State	Varies
Odor	Sweet
VOC Content	45% - 77% by weight
Flash Point	81°F
Dry Time	25-35 seconds *Note: Drying time may vary depending on film

## AVAILABLE IN

Color	Units/Case	Marker Tip	Part #
black	48	medium, felt (#16)	84202
blue	48	medium, felt (#16)	84201
green	48	medium, felt (#16)	84207
red	48	medium, felt (#16)	84206
orange	48	medium, felt (#16)	84205
white	48	medium, felt (#16)	84203
yellow	48	medium, felt (#16)	84204



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS<sup>®</sup>, SCRUBS<sup>®</sup>, DYKEM<sup>®</sup>, Accu-Lube<sup>®</sup>, DYMON<sup>®</sup>, Spray Nine<sup>®</sup>, and Cedar<sup>®</sup> are registered trademarks and Rustlick<sup>™</sup>, Diamondkote<sup>™</sup>, and MetalMates<sup>™</sup> are trademarks of Illinois Tool Works • All Rights Reserved