



Instant Super Degreaser 2.0



FEATURES

- Non-flammable – can be used on or near energized equipment. This improves safety and reduces downtime associated with de-energizing equipment.
- Non-brominated – improved health and safety profile for increased worker safety and simplified employer compliance.
- Fast Evaporation – quickens clean-up time. Improves productivity and reduces downtime
- No Rinsing/No Residue – no wiping or rinsing prior to next production step, reduces time and labor.
- Heavy-duty Performance – removes oil, grease, dirt, and tar with less cleaner, saving money.
- Non-conductive – can be used on or near energized equipment, eliminating equipment downtime.
- Power Blast Spray – blasts away dirt, oil, and other residues for quicker cleaning (increased productivity).

APPLICATIONS

- Air Compressors
- Bearings
- Cables
- Chains
- Forklifts
- Gears
- Heavy Equipment
- Power Tools

SPECIFICATIONS AND APPROVALS

- NSF International, K1 (Aerosol)
- NSF International, K1 (Bulk)

PROPERTIES

Appearance / Physical State	Aerosol: Gas, Bulk: Liquid
Color	Colorless.
Odor	Ether-like.
Melting / Freezing Point	Not available.
Boiling Point / Range	122.83 °F (50.46 °C)
Flash Point	None – Tag Closed Cup
Evaporation Rate	Not applicable.
Flammability	Non flammable gas/Not applicable.
Vapor Pressure	Not available.
Vapor Density	3.67 (air = 1)
Water Solubility	Not available.
Partition Coefficient	Not available.
Auto-Ignition Temperature	Not available.
Viscosity	Not applicable.
Percent volatile	100%
Specific Gravity	Aerosol: Not available, Bulk: 1.28
Density	Aerosol: 11.06 lb/gal, Bulk: Not available.
VOC Content	Aerosol: 96.5%, Bulk: 100% per US Federal Consumer Product Regulations
Propellant	Aerosol: Carbon dioxide, Bulk: Not applicable.

DIRECTIONS

Aerosol - Spray on parts and equipment. Allow flushing action to dissolve and remove contaminants. Bulk - Use in dip or spray applications. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure. In food plants, use in non-food handling areas only. Wash with an acceptable detergent solution and thoroughly rinse with potable water before returning equipment to a processing area.

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Close valve after each use and when empty. Protect containers from physical damage; do not drag, roll, slide, or drop. When moving containers, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport containers. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices (see Section 7 of the SDS).

STORAGE

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Store locked up. Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst (see Section 7 of the SDS).

DISPOSAL

Aerosol - Contents under pressure. Do not puncture, incinerate or crush. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
07220	C07220	20 wt oz / 567 g / 437 mL	aerosol	12	19 lbs
07255	C07255	55 gal / 208 L	drum	1	369 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved