



FEATURES

- Non-flammable, odorless, and leaves no residue .
- Quick blast precision duster
- Excellent for use on delicate mechanisms and energized electrical eauipment
- Moisture free
- Includes with pinpoint extension tube to be used in hard-to-reach spaces
- Removes contaminants, dirt, dust, and other soils
- New Propellant with Lower Global Warming Potential <i>Global Warming Potential 100-yr rev. 5 IPPC (GWP CO2 = 1): Previous propellant (HFC-134a) = 1300 New propellant (HFO-1234ze) = <1</i>

APPLICATIONS

• Avionics Computers

- Film Negatives
- Data Processing Equipment Electronic Equipment
- Industrial • Industrial Magnetic Tape Heads
- Laboratory Instruments

PROPERTIES

| Appearance / Physical State Gas Color Colorless Odor Slight. Ether-like. Melting / Freezing Point Not available. Boiling Point / Range -2.2 °F (-19 °C) Flash Point Not applicable. Evaporation Rate Not applicable. Flammability Lower Explosive line | | | |
|--|--|--|--|
| Odor Slight. Ether-like. Melting / Freezing Point Not available. Boiling Point / Range -2.2 °F (-19 °C) Flash Point Not applicable. Evaporation Rate Not applicable. Flammability Lower Explosive lite | | | |
| Melting / Freezing Point Not available. Boiling Point / Range -2.2 °F (-19 °C) Flash Point Not applicable. Evaporation Rate Not applicable. Flammability Lower Explosive line | | | |
| Boiling Point / Range -2.2 ° F (-19 °C) Flash Point Not applicable. Evaporation Rate Not applicable. Flammability Lower Explosive line | | | |
| Flash Point Not applicable. Evaporation Rate Not applicable. Flammability Lower Explosive li | | | |
| Evaporation Rate Not applicable. Flammability Lower Explosive li | | | |
| Flammability Lower Explosive li | | | |
| | | | |
| 20°C; 5.7 % at 60° Explosive limit (%) 11.3 % at 60°C | C Upper | | |
| | 4271 hPa @ 20°C (68°F) 11152 hPa @ 54.4°C (129.9°F) | | |
| Vapor Density 4 | | | |
| Density Not available. | Not available. | | |
| Water Solubility 0.37 g/l @ 25°C | 0.37 g/l @ 25°C | | |
| Partition Coefficient > 1 | >1 | | |
| Auto-Ignition Temperature 694.4°F (368°C) | 694.4°F (368°C) | | |
| Viscosity Not established. | Not established. | | |
| Heat of Combustion < 20 kJ/g | < 20 kJ/g | | |
| Percent volatile 100% | 100% | | |
| Specific Gravity 1.17 @ 21.1°C | 1.17 @ 21.1°C | | |
| | 0% per State & Federal Consumer Product Regulations | | |
| Propellant HFO-1234ze | | | |

DIRECTIONS

Hold can in upright position. Spray in short bursts until contaminants are removed. Do not tilt, invert or shake can during use. For precision applications, use attached extension tube.

HANDLING

Avoid breathing vapors. Avoid skin contact with liquid product. Vapors are heavier than air. Keep out of reach of children.

STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Contents under pressure. Keep away from heat, sparks and open flame. Keep container tightly closed. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). Store aerosols as Level 1 Aerosol (NFPA 30B).

DISPOSAL

Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations.

AVAILABLE PRODUCTS

| Part No. | | | Contain on Tomo | | • • • • • • • • • • • • • • • • • • • |
|----------|--------|------------------------------|-----------------|------------|---------------------------------------|
| US | Canada | Net Contents | Container Type | Units/Case | Approximate Case |
| | | | | | Weight |
| 05710 | C05710 | 12 wt oz / 340 g / 281 mL | aerosol | 12 | 11 lbs |



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved