



VO-45

Straight oil

FEATURES

- Light-Duty vanishing oil w/low VOC content

APPLICATIONS

- Straight oil / vanishing oil used for copper/brass components and other light-duty stamping operations

DIRECTIONS

Metal Mates VO-45 is supplied ready to use. Do not dilute.

HANDLING

Use appropriate safety equipment. Use with adequate ventilation. Avoid contact with eyes, skin and clothing. Keep away from extreme heat. Keep container closed when not in use.

STORAGE

Store away from extreme heat, flame, or ignition sources. Pressure buildup may occur due to heat exposure or temperature change. Release pressure by slowly opening container.

DISPOSAL

Absorb on suitable material and follow procedures listed below. Dispose of in a manner that is recommended by local, state, provincial and federal laws and regulations.



PROPERTIES

pH Value	Not applicable
Specific Gravity	0.805
Flash Point	>200F (>93C)
Boiling Point / Range	212F (100C)
Melting / Freezing Point	212F (100C)
Vapor Pressure	<1
Vapor Density	Heavier than air
Prop 65 Warning	No

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Color
MM5152	5 Gallon	Pail	1	Petroleum
MM5153	55 gal	drum	1	petroleum odor
MM5156	330 Gallon	Tote	1	petroleum



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved