



WS-11 Water-Soluble Oil

DESCRIPTION

Economical water-soluble oil for light-duty use

FEATURES

- Water-soluble oil
- Economical general-purpose
- Great lubricity
- General purpose coolant
- Thin oily-film corrosion protection
- Increases tool life

APPLICATIONS

- Light-duty operations
- General machining and grinding

MATERIALS COMPATIBILITY

- Ferrous Metals
- Aluminum
- Limited use on Stainless Steel.
- Limited use on Titanium.
- Limited use on Brass, Bronze, and Copper.

DIRECTIONS

FOR PRODUCT/APPLICATOR TROUBLE SHOOTING:
Use a refractometer to measure coolant concentration.
Use Triadine 20 or Grotan for microbial control in sump tanks. Call Technical Sales for detailed questions pertaining to the products.



PROPERTIES

Appearance / Physical State	Dark brown
Class	Water-Soluble Oil
pH Value	9
Specific Gravity	0.92
Density	7.7 lbs/gal
Flash Point	320°F (160°C)
Total Chlorine	None
Mineral Oil	85.00%
Water Solubility	Soluble
Dilution Ratio	General Machining and Grinding: 10:1-30:1
Refractometer Readings	10:1 = 10.5 20:1 = 5.3 30:1 = 3.5

SHELF LIFE INFORMATION

1 year

AVAILABLE PRODUCTS

Part No.	Net Contents	Units/Case
74553	55 gal	1
74053	5 gal	1
74013	1 gal	4



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved